





nse
K51300.02.TR.BK-BK.45.ST.9.30



GENERAL DETAILS

INSTALLATION	Trimless
COLOR EXT-INT	Black-Black
LIGHT DIRECTION	Fixed
BEAM ANGLE	45°
INT/EXT IP DEGREE	IP20
MATERIAL	Aluminio
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 años

ELECTRICAL DETAILS

LAMP	LED
POWER	10W
COLOUR TEMPERATURE	2700K
ANALYSIS LUMINAIRE LUMINOUS FLU	640 Lm
ANALYSIS EFFICIENCY	55 Lm/W
DIMABLE	No Dim
DRIVER	Remoto
ELECTRICAL INSULATION CLASS	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	700 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSION	137×35 mm
CUT OUT	143×70 mm
HEIGHT	h 56.5 mm
ALTURA MIN DE FALSO TECHO	20 mm
DISTANCIA MIN FALSO TECHO	20 mm
DIMENSIONES DE EMBALAJE	190 × 80 × 85 mm
PESO NETO	0.48

