




nses tilt
K51301.03.RF.WH-BK.30.ST.9.27

GENERAL DETAILS

INSTALLATION	recessed with frame
COLOR EXT-INT	Black-White
LIGHT DIRECTION	Orientable
BEAM ANGLE	30°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminio
TILTING DEGREES	90°
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 años

ELECTRICAL DETAILS

LAMP	LED
POWER	20 W
COLOUR TEMPERATURE	4000K
ANALYSIS LUMINAIRE LUMINOUS FLU	1250 Lm
ANALYSIS EFFICIENCY	63 Lm/W
DIMABLE	No Dim
DRIVER	Remoto
ELECTRICAL INSULATION CLASS II	
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	700 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSION	300×58 mm
CUT OUT	290×45 mm
HEIGHT	h 48.5 mm
DISTANCIA MIN FALSO TECHO	20 mm
DIMENSIONES DE EMBALAJE	325 × 80 × 85 mm
PESO NETO	0.78

*Please might expect a max.15% figure reduction in finishes other than white

