



ITEM	DESCRIPTION
1	MOUNTING PLATE
2	EXPANSION SCREW
3	SMALL HEX NUT
4	HEX NUT
5	NIPPLE
6	SWIVEL
7	CANOPY
8	TERMINAL BLOCK
9	STEM
10	FIXTURE ASSEMBLY
11	THREADED RING
12	BULB

⚠ WARNING/CAUTION

- **DISCONNECT POWER BEFORE RE-LAMPING OR WIRING THE FIXTURE. READ ALL INSTRUCTIONS COMPLETELY BEFORE STARTING INSTALLATION.**
- **TO AVOID THE RISK OF FIRE OR SHOCK, FIXTURE MUST BE INSTALLED IN COMPLIANCE WITH ALL APPLICABLE NATIONAL AND LOCAL ELECTRICAL/BUILDING CODES. THE INSTALLATION AND MAINTENANCE OF THIS UNIT SHOULD BE COMPLETED BY A LICENSED ELECTRICIAN OR CERTIFIED FACTORY TRAINED TECHNICIAN.**
- **REMOVE THE FIXTURE, PARTS AND PARTS BAG(S) FROM THE CARTON. BEFORE DISCARDING THE CARTON, DOUBLE CHECK TO MAKE CERTAIN THAT ALL PARTS ARE FOUND. INSPECT THE FIXTURE PRIOR TO INSTALLATION FOR ANY DAMAGE TO THE FIXTURE.**
- **DIMMING: THE FIXTURE CAN BE CONTROLLED BY A WALL DIMMING DEVICE. ONLY USE TRIAC/ELECTRONIC DIMMER. MAKE SURE THE CARTON IS MARKED FOR USE WITH LED COMPACT FLUORESCENT-INCANDESCENT LIGHT SOURCE ONLY. THESE CAN BE PROVIDED BY YOUR LOCAL ELECTRICAL DISTRIBUTOR, HOME CENTER, OR HARDWARE STORE.**
- **PLEASE CLEAN WITH A SOFT, DRY CLOTH ONLY! DO NOT USE CLEANSERS**

FIXTURE INSTALLATION

1. Feed the wires through the STEM (9) and twist tightly onto the FIXTURE ASSEMBLY (10). Keep adding additional stems until you desired hanging height is met.
2. Thread the SWIVEL (6) onto the top end of the STEM (9). Unscrew the THREADED RING (11) from the SWIVEL (6) then slide it down the STEM (9).
3. Slide the CANOPY (7) onto the STEM (9).
4. Pull the wire out from the junction box, and install the MOUNTING PLATE (1) onto the junction box or ceiling using the supplied EXPANSION SCREW (2) and SMALL HEX NUT (3). Thread the NIPPLE (5) in the MOUNTING PLATE (1), then secure using HEX NUT (4).
6. Thread the SWIVEL (6) to the NIPPLE (5).
7. Open the TERMINAL BLOCK (8).
8. Fasten the neutral wire from the junction box to the TERMINAL BLOCK (8), run it through the insulation tube and align it to the fixture blue wire. (See the figure by the left for reference) **MAKE SURE THERE ARE NO EXPOSED WIRE OF STRANDS THAT COULD CAUSE A DANGEROUS SHORT CIRCUIT!**
9. Fasten the live wire from the junction box to the TERMINAL BLOCK (8), run it through the insulation tube and align it to the fixture brown wire. (See the figure by the left for reference) **MAKE SURE THERE ARE NO EXPOSED WIRE OF STRANDS THAT COULD CAUSE A DANGEROUS SHORT CIRCUIT!**
10. Fasten the ground wire from the junction box to the TERMINAL BLOCK (8), run it through the insulation tube and align it to the fixture green wire. (See the figure by the left for reference) **MAKE SURE THERE ARE NO EXPOSED WIRE OF STRANDS THAT COULD CAUSE A DANGEROUS SHORT CIRCUIT!**
11. Close the TERMINAL BLOCK (8).
12. Attach the TERMINAL BLOCK (8) to the mounting assembly.
13. Lift the CANOPY (7) up to the ceiling, and secure with THREADED RING (11).
14. Install the BULB (12) into the socket of the FIXTURE ASSEMBLY (10). **THIS FIXTURE IS RATED FOR 40 WATT 220 VOLT LAMP. DO NOT EXCEED THE RECOMMENDED WATTAGE!**
15. Restore power to the circuit breaker or fuse box.