



nses tilt
K51301.01.RF.BK-BK.30.ST.9.30

GENERAL DETAILS

INSTALLATION	recessed with frame
COLOR EXT-INT	Black-Black
LIGHT DIRECTION	Orientable
BEAM ANGLE	30°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminio
TILTING DEGREES	90°
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 años

ELECTRICAL DETAILS

LAMP	LED
POWER	6 W
COLOUR TEMPERATURE	3000K
ANALYSIS LUMINAIRE LUMINOUS FLU	335 Lm
ANALYSIS EFFICIENCY	49 Lm/W
DIMABLE	No Dim
DRIVER	Remoto
ELECTRICAL INSULATION CLASS II	
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	700 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSION	123×58 mm
CUT OUT	115×45 mm
HEIGHT	h 48.5 mm
DISTANCIA MIN FALSO TECHO	20 mm
DIMENSIONES DE EMBALAJE	190 × 80 × 85 mm
PESO NETO	0.35

*Please might expect a max.15% figure reduction in finishes other than white

