



nses tilt  
K51301.03.RF.BK-BK.45.ST.9.40

## GENERAL DETAILS

|                   |                     |
|-------------------|---------------------|
| INSTALLATION      | recessed with frame |
| COLOR EXT-INT     | Black-Black         |
| LIGHT DIRECTION   | Orientable          |
| BEAM ANGLE        | 45°                 |
| INT/EXT IP DEGREE | IP 23               |
| MATERIAL          | Aluminio            |
| TILTING DEGREES   | 90°                 |
| IK DEGREE         | IK 6                |
| UTILIZATION       | Indoor              |
| WARRANTY          | 3 años              |

## ELECTRICAL DETAILS

|                                    |           |
|------------------------------------|-----------|
| LAMP                               | LED       |
| POWER                              | 20 W      |
| COLOUR TEMPERATURE                 | 3000K     |
| ANALYSIS LUMINAIRE LUMINOUS<br>FLU | 1470 Lm   |
| ANALYSIS EFFICIENCY                | 73 Lm/W   |
| DIMABLE                            | No Dim    |
| DRIVER                             | Remoto    |
| ELECTRICAL INSULATION CLASS II     |           |
| COLOUR RENDERING INDEX             | CRI>90    |
| VOLTAGE                            | 220-240 V |
| FRECUENCIA                         | 50-60 Hz  |
| CURRENT INTENSITY                  | 700 mA    |
| LIFE TIME                          | 35.000 h  |

## GENERAL DIMENSIONS

|                           |                  |
|---------------------------|------------------|
| DIMENSION                 | 300×58 mm        |
| CUT OUT                   | 290×45 mm        |
| HEIGHT                    | h 48.5 mm        |
| DISTANCIA MIN FALSO TECHO | 20 mm            |
| DIMENSIONES DE EMBALAJE   | 325 × 80 × 85 mm |
| PESO NETO                 | 0.78             |

\*Please might expect a max.15% figure reduction in finishes other than white

