


**disc sq**  
K51703.03.RF.BK-BK.OP.ST.8.40



## GENERAL DETAILS

|                   |                     |
|-------------------|---------------------|
| INSTALLATION      | recessed with frame |
| COLOR EXT-INT     | Black-Black         |
| LIGHT DIRECTION   | Fixed               |
| INT/EXT IP DEGREE | IP 43               |
| MATERIAL          | Aluminio            |
| IK DEGREE         | IK03                |
| UTILIZATION       | Indoor              |
| WARRANTY          | 3 años              |

## ELECTRICAL DETAILS

|                                 |           |
|---------------------------------|-----------|
| LAMP                            | LED       |
| POWER                           | 20 W      |
| COLOUR TEMPERATURE              | 4000K     |
| ANALYSIS LUMINAIRE LUMINOUS FLU | 1800 lm   |
| ANALYSIS EFFICIENCY             | 92 Lm/W   |
| DIMABLE                         | No Dim    |
| DRIVER                          | Remoto    |
| ELECTRICAL INSULATION CLASS II  |           |
| COLOUR RENDERING INDEX          | CRI >80   |
| VOLTAGE                         | 220-240 V |
| FRECUENCIA                      | 50-60 Hz  |
| CURRENT INTENSITY               | 500 mA    |
| LIFE TIME                       | 35.000 h  |

## GENERAL DIMENSIONS

|                           |                   |
|---------------------------|-------------------|
| DIMENSION                 | 225×225 mm        |
| CUT OUT                   | 205X205 mm        |
| HEIGHT                    | h 20mm            |
| DISTANCIA MIN FALSO TECHO | 20 mm             |
| DIMENSIONES DE EMBALAJE   | 202 × 210 × 45 mm |
| PESO NETO                 | 0.40              |

\*Please might expect a max.15% figure reduction in finishes other than white