

LED Switching Power Supply

- Conversion efficiency: 94%;
- Crimp type wiring, flexible installation;
- High power density, small size, high only 22.6mm, saving installation space;
- 100% full load burn-in test,
- Suitable for internal lights application for I / II / III.
- Equipped with over temperature, over current protection, short circuit protection, UVP, OVP
- Widely used in LED lighting and IT equipment
- Compliance to worldwide safety regulation for led lightings.



SELV




Specification


Model		NANO-12-300	NANO-24-300	NANO-36-300	NANO-48-300
OUTPUT	Output voltage	12VDC	24VDC	36VDC	48VDC
	Output voltage range	12VDC±0.5VDC	24VDC±0.5VDC	36VDC±0.5VDC	48VDC±0.5VDC
	Output current	Max 25A	Max 12.5A	Max 8.33A	Max 6.25A
	Output power	Max 300W			
	Output power range	0~300W			
	Linear Regulation	±1%			
	Load Regulation	±1%			
	Start-up Time [Typ]	500ms/230Vac			
	Hold Up Time [Typ]	12ms/230Vac			
INPUT	Input voltage	200~240Vac			
	Frequency	50Hz			
	Input current	2.2A/230Vac			
	Power factor	PF>0.65			
	No-load power consumption	< 0.75W			
	Efficiency (typ.)	93%	94%	94%	94%
	Inrush current(typ.)	Cold start 65A at 230Vac			
	Control surge capability	L,N:1KV L,N-PE:2KV			
	Leakage current	Max. 0.5mA			
ENVIRONMENT	Working temperature	ta: -30°C~ 50°C tc: 80°C			
	Working humidity	20 ~ 99%RH, non–condensing			
	Storage temp., humidity	-40°C ~ 80°C, 10~95%RH			
PROTECTION	Over load protection	Shut down the output when current load ≥110%~150%, auto recovers.			
	Short circuit protection	Protection type: It can be automatically restored after the fault is eliminated.			
SAFETY & EMC	Withstand voltage	I/P-O/P:3000Vac			
	Isolation resistance	I/P-O/P: 100MΩ/500VDC/25°C/70%RH			
	EMC Test Standards	EN55015: 2013;EN61547: 2009; EN61000-3-2:2014; EN61000-3-3:2013			
Reliability and Quality Control	Impact aging	100% of the product is fully loaded and impacted for 4 hours under an environment of at least 40°C ± 5°C			
	Component derating	Under the steady-state conditions of rated input and output, the stress of components will not exceed its maximum nominal value			
NOTE	1. All parameters not specifically mentioned are measured at 230VAC input, rated load and 25°C ambient temperature. 2. Ensure that the power supply is used under the rated parameters and environment.				

Dimensions

Unit:mm




Relationship diagrams



Packaging Information

DIMENSION	305x31.3x22.6mm(LxWxH)
PACKING	mm(LxWxH)
CARTON QUANTITY	PCS
CARTON SIZE	mm(LxWxH)
WEIGHT	393g±10g/PCS



* No further notice if any changes in the manual. Product function depends on the goods. Please feel free to contact your supplier if any question.